



# TECHNISMART remote control

Remote control for communication with TECHNISMART 1 base

Colour	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
grau/schwarz	4019588095618	0000/9561	30 g	20 g	7,44 x 3,45 x 1,61 cm	8,2 x 2 x 5,5 cm

## TOP FEATURES

Remote control for TECHNISMART alert system

Theft and tamper protection

Simple connection via TECHNISMART App

433,92 MHz wireless technology

Alerts events defined in the smart home system

Component for the TECHNISMART alert system

Cordless battery operation

## WLAN

WLAN: Ja (802.11ac)

## AMBIENT OPERATING CONDITIONS

Ambient temperature: -10 ... 45 °C

Humidity: 10 ... 75 %

## BLUETOOTH VERSION & PROFILE

Bluetooth version: 5

## CONNECTIONS

Ethernet 10/100 (RJ-45): Yes

DC IN: 1

USB: 2

## FUNK COMMUNICATION

Telecommunication: RF (ISM-Band)

Range inside: max. 30 m

Range outside: max. 100 m

operating frequency: 433,92 MHz

## NETWORK & COMMUNICATION

Bluetooth: Yes 4.1 LE

#### OPERATION POSSIBILITIES

Tablet PC: Ja

Smartphone: Ja

#### OTHER FEATURES

OSD languages: English, German

#### POWER SUPPLY

Battery life: up to 120 min pro Akkuladung auf niedrigster Stufe

Nominal voltage: 3 V

Frequency: 50 Hz

Mains adapter: DC 18 V / 3.300 mA

Rechargeable battery: Lithium ions with 14,4 V, 2.600 mAh und 37,44 Wh

Effective output: 3 W

Non rechargeable battery: CR2032

Type of power supply: External

#### SCOPE OF DELIVERY

Remote control