



TECHNIVISION 26 HD

Full-HD Digital TV with eLED panel and HDTV multituner including digital DVR function via USB to record TV and radio broadcast on an external hard drive

| Weight without stand | EAN | Colour | Item no. | Weight (Box) | Weight | Unit without stand (W x H x D) | Device (W x H x D) | Box |
|----------------------|---------------|--------------|-----------|--------------|--------|--------------------------------|---------------------|---------------------|
| 6,4 kg | 4019588267329 | black | 5026/7326 | 10 kg | 7 kg | 649 x 438 x 48 mm | 64,9 x 49 x 20,5 cm | 72,5 x 57,5 x 25 cm |
| 6,4 kg | 4019588267305 | silver/black | 5026/7306 | 9 kg | 9 kg | 649 x 438 x 48 mm | 64,9 x 49 x 20,5 cm | 72,5 x 57,5 x 25 cm |

TOP FEATURES

HDTV multituner

Digital video recorder function via USB (DVRready)

Timeshift (in conjunction with an external storage medium)

PerfectRecording

LED display with clock

Common Interface Plus (CI+)

AMBIENT OPERATING CONDITIONS

Humidity: 10 - 75 %

Ambient temperature: 5 - 35 °C

LNB CONTROL

Band switch: 22 kHz

Vertical: <14 V without load, > 11.5 V at 400 mA V

DiSEqC: DiSEqC 1.0 and 1.2 / DiSEqC 1x Sat Channel Router

Current consumption: max (kurzschlussfest) 400 mA

Horizontal: <20 V without load, > 17.2 V at 400 mA V

TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL: Yes

AUDIO

AC3 Dolby Digital bitstream out: Yes

Speakers: integrated broadband speaker system

CONNECTIONS

HDMI™ (in): 2

Common Interface Plus (CI+): Yes

Digital electric audio output (S/PDIF): Yes Cinch

Audio in/AUX in: Yes 3.5mm Klinke

VGA: Yes

YUV (component input): Yes Cinch

Scart: 1 (FBAS/RGB)

S Video: Yes

Video IN: 1 Cinch Composite

F socket: 1

IEC-Connector: Yes

DECRYPTION SYSTEM

CI+: Yes

DIMENSIONS / WEIGHT

Set width without stand: 649 mm

Weight without stand: 6,4 kg

Set height without stand: 438 mm

Set depth without stand: 48 mm

DISPLAY

Size (cm): 66 cm

Frequency: 50 Hz

Format: 16:9

Contrast ratio: 800:1

Brightness: 400 cd/m²

Response time: 5 ms

Angle of view: 150° V / 160° H

Freeze frame: Yes

HD: Yes

Type: Full-HD eLED

1080i: Yes

Resolution (vertical and horizontal): 1920 x 1080

720p: Yes

SD: Yes

Size (inches): 26

HANDLING/COMFORT

Alarm: Yes

Clock: Yes

Sleep timer: Yes

HOTEL MODE

Customisable start screen: Yes

Configurable on times: Yes

Energy card function: Yes

USB cloning function: Yes

Multimedia connectors: Yes

Menu locking: Yes

Integrated LED clock: Yes

Radio mode: Yes

Mixing of channel slots: Yes

Multicode remote control: Yes

Fireproofed housing: Yes

MATERIALS CONTAINED

Lead: Yes

OTHER FEATURES

OSD languages: German, Spanish, Hungarian, Czech, Portuguese, Turkish, Polish, French, Italian, Russian, English, Greek, Swedish, Dutch

Total programme memory: 5.000

Regional channel selection: Yes

POWER CONSUMPTION

SFlplus updating: 19,8 W

Software update: 19,8 W

Energy class: B

Standby fast start: 19 W

Standby LED: 0,64 W

In operation: 42 W

annual energy consumption when switched on: 61 kilowatt hour per annum

Off status: 0 W

Power switch: Yes

TUNER

Tuner type: HDTV-Multituner

DVB-S tuner: 1

DVB-C Tuner: 1

DVB-T Tuner: 1

Analogue UHF/VHF/CATV tuner: 1

TECHNIROUTER ready: Yes

Input impedance: 75 Ω

Reception on: HDTV (Mpeg-4+2) SD (MPEG-2)

TUNER - SAT

Viterbi rates: 1/2, 2/3, 3/4, 5/6, 7/8

Reception range: 950 ... 2.150 MHz

DVB-S2: 8PSK - QPSK

DVB-S: QPSK

DVB-S: 2 ... 45

DVB-S2: 10 ... 31

FEC: Viterbi and Reed-Solomon

POWER SUPPLY

Nominal voltage: 230 V

Frequency: 50 Hz

Mains adapter: internal

TUNER - ANALOGUE

Video standards: B/G stereo, D/K mono, L/L¹

Reception range: 47 ... 862 MHz

TUNER - TERRESTRIAL

Reception range 2: 470 ... 860 MHz

Transmission mode: 2k/8k

Demodulation: COFDM

Power supply: 0,05 A

Reception range 1: 174 ... 230 MHz

Voltage supply: 5 V

Bitrate: 4 ... 32

SUPPORTED FORMATS & CODECS

MPEG-2: Yes

Video-Formats: TS4, TS, VOB

JPEG: Yes

MP3: Yes

TUNER - CABLE

Demodulation: 16/32/64/128/256 QAM

Reception range: 51 ... 858 MHz

Symbol rate: 1,7 ... 7

FEC: Reed-Solomon

WALL BRACKET

VESA wall mounting standards: VESA 100 x 100

SCOPE OF DELIVERY

TechniVision 26 HD, Stand, 230 V mains power cable, TechniControl remote control incl. batteries, Manual

Test Results TECHNIVISION 26 HD



Test-Sieger
PC-Welt (07/2011)