



## TECHNISMART RFID Keypad

RFID Keypad for TECHNISMART 1

Colour	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
Wei	4019588095649	0000/9564	300 g	180 g	9 x 14,5 x 2,5 cm	9,5 x 15 x 6 cm

### TOP FEATURES

- Expansion for the TECHNISMART alarm system: To use the RFID keypad, the TECHNISMART central unit and the free TECHNISMART app (iOS) are required
- The external control panel is used to arm or disarm the alarm system. Instead of entering a code, authorization can also be done via RFID tag (optional)
- Battery or mains: Power can be supplied wirelessly via battery (approx. 6 months runtime) or continuously via power supply. The indoor keypad is easily wall-mounted with screws
- Intuitive operation and easy setup: The keypad integrates into the TECHNISMART alarm system via a simple QR code scan using the free TECHNISMART app

### WLAN

WLAN: Ja (802.11ac)

### AMBIENT OPERATING CONDITIONS

Humidity: 10 ... 75 %

Ambient temperature: -10 ... 45 °C

### BLUETOOTH VERSION & PROFILE

Bluetooth version: 5

CONNECTIONS		FUNK COMMUNICATION		NETWORK & COMMUNICATION			
Ethernet 10/100 (RJ-45): Yes		Telecommunication: RF (ISM-Band)		Bluetooth: Yes 4.1 LE			
DC IN: 1		Range inside: max. 30 m					
USB: 1		Range outside: max. 100 m					
		operating frequency: 433,92 MHz					
OPERATION POSSIBILITIES		OTHER FEATURES		POWER SUPPLY		SCOPE OF DELIVERY	
Tablet PC: Ja		OSD languages: English, German		Battery life: up to 6 months		RFID keypad, power adapter,	
Smartphone: Ja				Nominal voltage: 230 V		installation material	
				Frequency: 50 / 60 Hz			
				Mains adapter: 5V - 1A			
				Rechargeable battery: Lithium ions with 3,7 V / 800 mAh / 2,96 Wh BL-5B			
				Effective output: 3 W			
				Non rechargeable battery: 2 x 1,5 V Alkaline, AAA, Klasse III			
				Type of power supply: external			