



## TECHNISMART door/window contact

Door/Window contact switch to proof if the door resp. the window is closed or not for TECHNISMART 1.

Colour	VPE Palette	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
Weiß	0	4019588095625	0000/9562	60 g	32 g	8,5 x 2,5 x 2,5 cm	10,6 x 2,5 x 5,5 cm

### TOP FEATURES

Magnetic door/window contact

Theft and tamper protection

Simple connection via TECHNISMART App

433,92 MHz wireless technology

Detecting the closing state of doors or windows

Component for the TECHNISMART 1 alert system

Cordless battery operation

Compact, discreet design

### WLAN

WLAN: Ja (802.11ac)

### AMBIENT OPERATING CONDITIONS

Ambient temperature: -10 ... 45 °C

Humidity: 10 ... 75 %

### BLUETOOTH VERSION & PROFILE

Bluetooth version: 5

### CONNECTIONS

Ethernet 10/100 (RJ-45): Yes

DC IN: 1

USB: 2

### FUNK COMMUNICATION

Telecommunication: RF (ISM-Band)

Range inside: max. 30 m

Range outside: max. 100 m

operating frequency: 433,92 MHz

### NETWORK & COMMUNICATION

Bluetooth: Yes 4.1 LE

#### OPERATION POSSIBILITIES

Tablet PC: Ja

Smartphone: Ja

#### OTHER FEATURES

OSD languages: English, German

#### POWER SUPPLY

Nominal voltage: 3 V

Battery life: up to 120 min pro Akkuladung auf niedrigster Stufe

Frequency: 50 Hz

Rechargeable battery: Lithium ions with 14,4 V, 2.600 mAh und 37,44 Wh

Mains adapter: DC 18 V / 3.300 mA

Effective output: 3 W

Non rechargeable battery: CR123A

Type of power supply: External

#### SCOPE OF DELIVERY

Door/Window contact, installation material