



## TECHNISMART door/window contact

Door/Window contact switch to proof if the door resp. the window is closed or not for TECHNISMART 1.

Colour	VPE Palette	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
Weiβ	0	4019588095625	0000/9562	60 g	32 g	8,5 x 2,5 x 2,5 cm	10,6 x 2,5 x 5,5 cm

### TOP FEATURES

- Expansion for the TECHNISMART alarm system: To use the door/window contact, the TECHNISMART central unit and the free TECHNISMART app (iOS) are required
- Compact, discreet design: The magnetic door/window contact is easily mounted using adhesive strips—no drilling or screwing required. Operates wirelessly via battery
- Detects door or window open status: If a door or window is opened while the alarm system is armed, an acoustic alarm is triggered via the central unit and/or a notification sent to your smartphone
- Intuitive operation and easy setup: The door/window contact integrates into the TECHNISMART alarm system via a simple QR code scan using the free TECHNISMART app

### WLAN

WLAN: Ja (802.11ac)

### AMBIENT OPERATING CONDITIONS

Ambient temperature: -10 ... 45 °C

Humidity: 10 ... 75 %

### BLUETOOTH VERSION & PROFILE

Bluetooth version: 5

CONNECTIONS	FUNK COMMUNICATION	NETWORK & COMMUNICATION	
Ethernet 10/100 (RJ-45): Yes	Telecommunication: RF (ISM-Band)	Bluetooth: Yes 4.1 LE	
OPERATION POSSIBILITIES	OTHER FEATURES	POWER SUPPLY	SCOPE OF DELIVERY
Tablet PC: Ja	OSD languages: English, German	Nominal voltage: 3 V	Door/Window contact, installation material
Smartphone: Ja		Battery life: up to 120 min pro Akkuladung auf niedrigster Stufe	
		Frequency: 50 Hz	
		Rechargeable battery: Lithium ions with 14,4 V, 2.600 mAh und 37,44 Wh	
		Mains adapter: DC 18 V / 3.300 mA	
		Effective output: 3 W	
		Non rechargeable battery: CR123A	
		Type of power supply: External	