

UNIX Octo LNB

High-quality Octo converter for satellite installations with eight receivers.

Colour	EAN	Item no.
beige/orange	4019588764859	76-4805-00

TOP FEATURES

- Top-class HD and UHD signal reception performance
- Simple and quick assembly
- High quality housing resistant to difficult weather conditions
- Very low noise figure
- Perfect for installations with four TWIN LNBs
- Up to 8 users
- Low power consumption

NOISE FACTOR

Noise figure: 0,1 dB

OUTPUT FREQUENCY RANGE

Low band: 950 ... 1.950 MHz

High band: 1.100 ... 2.150 MHz

INPUT FREQUENCY RANGE

Low band: 10,7 ... 11,7 GHz

High band: 11,7 ... 12,75 GHz

AMBIENT OPERATING CONDITIONS

Ambient temperature: -30 ... 70 °C

Humidity: 10 ... 90 %

LNB CONTROL

Vertical: 10,5 ... 14 V

Horizontal: 16 ... 19 V

Band switch: 22 kHz

LOCAL OSCILLATOR

Low band: 9,75 GHz

High band: 10,6 GHz

TECHNICAL DATA
Outputs: 8
Amplification: 55 dB
Impedance: 75 Ω
Connector type: F connector
Feed reception: 40 mm

POWER SUPPLY
LNB voltage supply: 10,5 ... 19 V
Power consumption: max. 180 mA

SCOPE OF DELIVERY
UNIX Octo LNB