



## UNIX Octo LNB

High-quality Octo converter for satellite installations with eight receivers.

EAN	Colour	Item no.
4019588764859	beige/orange	76-4805-00

### TOP FEATURES

Top-class HD and UHD signal reception performance

Simple and quick assembly

High quality housing resistant to difficult weather conditions

Very low noise figure

Perfect for installations with four TWIN LNBS

Up to 8 users

Low power consumption

### LOCAL OSCILLATOR

Low band: 9,75 GHz

High band: 10,6 GHz

### LNB CONTROL

Vertical: 10,5 ... 14 V

Horizontal: 16 ... 19 V

Band switch: 22 kHz

### AMBIENT OPERATING CONDITIONS

Ambient temperature: -30 ... 70 °C

Humidity: 10 ... 90 %

### INPUT FREQUENCY RANGE

Low band: 10,7 ... 11,7 GHz

High band: 11,7 ... 12,75 GHz

### NOISE FACTOR

Noise figure: 0,1 dB

### OUTPUT FREQUENCY RANGE

Low band: 950 ... 1.950 MHz

High band: 1.100 ... 2.150 MHz

#### POWER SUPPLY

LNB voltage supply: 10,5 ... 19 V

Power consumption: max. 180 mA

#### TECHNICAL DATA

Outputs: 8

Amplification: 55 dB

Impedance: 75  $\Omega$

Connector type: F connector

Feed reception: 40 mm

#### SCOPE OF DELIVERY

UNIX Octo LNB