

DIGISPLITTER CE 3 HD

For 3-fold distribution or connection of satellite, terrestrial TV, cable and radio signals. The distributor has a constant tension grommet.

Colour	EAN	Item no.
silver	4019588769939	76-4993-00

TOP FEATURES

DC power pass

FILTER-NAVIGATION

Number satellites: 1

Number participants: 2

TRANSMISSION LOSS

5 - 862 MHz: Typ. 4,5 dB (± 1)

950 - 1750 MHz: Typ. 5 dB (± 1,5)

1750 - 2150 MHz: Typ. 6 dB (± 2)

RETURN LOSS

5 - 862 MHz: Typ. 12 dB

950 - 1750 MHz: Typ. 12 dB

1750 - 2150 MHz: Typ. 10 dB

TECHNICAL DATA

Input: 1

Outputs: 3

Frequency range: 5 ... 2.400 MHz

Shielding factor: ≥ 75 dB EN 50083-2 (Class A)

Connector type: F female

Impedance: 75 Ω

DECOUPLING

5 - 862 MHz: Typ. 22 dB (< 40 MHz = 8 dB)

950 - 1750 MHz: Typ. 20 dB

1750 - 2150 MHz: Typ. 20 dB

SCOPE OF DELIVERY

3-way satellite TV splitter