



DIGIT ISIO S4

HDTV satellite receiver with twin tuner

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588047679	black	0000/4767	1,29 kg	626 g	22 x 4 x 17,5 cm	31 x 8 x 19,5 cm

TOP FEATURES

HDTV twin tuner (DVB-S/S2)

Top quality OLED display

DVRready for recording on USB storage device

Timeshift in connection with USB hard drive

ISIO: Access to media libraries, online video stores, apps and HbbTV

Multimedia streaming on home network (via UPnP)

Control by CONNECT app

Pay TV compatible via CI+

Easy start-up via AutoInstall

Operation on 12V

MULTIMEDIA

DVR Function: Yes

DVR storage medium: via USB

Timeshift: Yes

Recordings edition function: Yes

Recordings folder management: Yes

FILTER-NAVIGATION

Reception type: Satellite (DVB-S/S2)

Connections: USB

Tuner type: Twin tuner

Resolution: Full HD

Features: App control

WLAN

WLAN: with optional WLAN-Adapter 0005/3633

AMBIENT OPERATING CONDITIONS

Ambient temperature: 5 ... 35 °C

Humidity: 10 ... 75 %

LNB CONTROL

Vertical: 14 V

Horizontal: 18 V

Band switch: 22 kHz

Current consumption: max. 400 mA (short-circuit proof)

DiSEqC: 1.0 / 1.2 / SCR1 / SCR2

TECHNISAT ADDED VALUE SERVICES

ISI-Mode: Yes

AUTOINSTALL: Yes

TECHNIMATIC: Yes

ISIPRO: Yes

TECHNIFAMILY: Yes

SFI: Yes

INTERNET/NETWORK

HTML 5 support: Yes

Internet speed test: Yes

Webbrowser: Yes

HbbTV: Yes

ISIO Internet: Yes

DECODER

Video decoder: MPEG-2 MP@HL/ML, H.264/MPEG-4 AVC

Audio decoder: MPEG-1 & MPEG-2 Layer I, II, III

HANDLING/COMFORT

Page memory: 1.000

Teletext subtitles: Yes

Media Player: Yes

Hotel mode: Yes

Remote control: Yes

Autostandby: Yes

Alarm: Yes

Teletext: Yes

Selection regional channels: Yes

Sleep timer: Yes

Ideal for camping: Yes

Channel presets: 9.999

Clock: Yes

OTHER FEATURES

OSD languages: German, Hungarian, Portuguese, Italian, Swedish, Greek, Spanish, Polish, English, French, Russian, Dutch, Czech, Turkish

AUDIO

Clear language from ARD: Yes via DVB

DECRYPTION SYSTEM

CI+: Yes

HOTEL MODE

Protected access to hotel mode: Yes

Customisable start screen: Yes

Lockable volume: Yes

Menu locking: Yes

Control panel lock: Yes

Integrated LED clock: Yes

Selectable start source: Yes

Selectable start channel: Yes

POWER CONSUMPTION

Standby LED: 0,4 W

In operation: 17,1 W

CONNECTIONS

HDMI™ (out): 1

USB: 2 (USB 2.0)

Common Interface Plus (CI+): Yes

Digital electric audio output (S/PDIF): Yes

F socket: 2

Connector for external IR-Receiver: 1

DC IN: 1

Ethernet 1Gbit/s (RJ-45): 1

DISPLAY

Picture in Picture (PIP): Yes (2x HD, 2x SD, 1x SD u. 1x HD)

Picture and Picture (PAP): Yes

Freeze frame: Yes

Zoom: Yes

SD: Yes

HD: Yes

1080p: Yes

1080i: Yes

720p: Yes

576p: Yes

576i: Yes

Type: 7-segments, 4-digits, white

NETWORK & COMMUNICATION

1000Base-T: Yes

IPv4: Yes

TCP/IP: Yes

RTP: Yes

DHCP: Yes

HTTPS: Yes

UDP: Yes

UPnP: Yes

HTTP: Yes

IGMP: Yes

POWER SUPPLY

Nominal voltage: 230 V

Frequency: 50 Hz

Mains adapter: external DC12V/3A

STREAMING

Cloud store: Ja

DLNA Client: Yes

Parental Control: Yes

DLNA Server: Yes

SUPPORTED FORMATS & CODECS

Video-CODECS: MPEG-2, MPEG-4, MPEG-1, H.264
(up to H.264/AVC Level 4.2)

Video-Formats: M4V, MP4, MKV, MOV, MPG,
MTS, TS, TS4, VOB, M2TS, AVI, ASF

Picture-Formats: BMP, JPEG, GIF, PNG

Audio-Formats: WAV, MP3, AAC, FLAC, M4A,
MP2, DDAC3, AIFF

TUNER

Tuner type: Twin-Tuner

DVB-S tuner: 2

Single Cable Solution (SatCR): SCR1 = EN50494,
SCR2 = EN50607

Satellite radio: Yes

Internet radio: Yes

Reception on: HD-TV, SD-TV

DVB-IP (multicast): 1

TECHNIROUTER ready: Yes

TECHNISELECT 12 ready: Yes

TUNER - SAT

Reception range: 950 ... 2.150 MHz

Viterbi rates: 1/2, 2/3, 3/4, 5/6, 7/8 , (auto)

DVB-S: QPSK

DVB-S: 2 ... 45

DVB-S2: 8PSK-QPSK

DVB-S2: 10 ... 31

FEC: RS, LDPC, BCH

SCOPE OF DELIVERY

DIGIT ISIO S4, remote control TechniControl including batteries, power supply,
HDMI cable, manual, warranty card

Test Results DIGIT ISIO S4



SATVISION 07/2023