

DIGIT ISIO S4

HDTV satellite receiver with twin tuner

Colour	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
black	4019588047679	0000/4767	1,29 kg	626 g	22 x 4 x 17,5 cm	31 x 8 x 19,5 cm

TOP FEATURES

- HDTV twin tuner (DVB-S/S2)
- Top quality OLED display
- DVRready for recording on USB storage device
- Timeshift in connection with USB hard drive
- ISIO: Access to media libraries, online video stores, apps and HbbTV
- Multimedia streaming on home network (via UPnP)
- Control by CONNECT app
- Pay TV compatible via CI+
- Easy start-up via AutoInstall
- Operation on 12V

MULTIMEDIA

- DVR function: Yes
- DVR storage medium: via USB
- Timeshift: Yes
- Recordings edition function: Yes
- Recordings folder management: Yes

FILTER-NAVIGATION

- Features: App control
- Resolution: Full HD
- Reception type: Satellite (DVB-S/S2)
- Tuner type: Twin tuner
- Connections: USB

WLAN

- WLAN: with optional WLAN-Adapter 0005/3633

AMBIENT OPERATING CONDITIONS

- Ambient temperature: 5 ... 35 °C
- Humidity: 10 ... 75 %

LNB CONTROL

- Vertical: 14 V
- Horizontal: 18 V
- Band switch: 22 kHz
- Current consumption: max. 400 mA (short-circuit proof)
- DiSEqC: 1.0 / 1.2 / SCR1 / SCR2

TECHNISAT ADDED VALUE SERVICES

- ISIPRO: Yes
- TECHNIMATIC: Yes
- AUTOINSTALL: Yes
- ISI-Mode: Yes
- TECHNIFAMILY: Yes
- SFI: Yes

INTERNET/NETWORK

ISIO Internet: Yes

Webbrowser: Yes

HTML 5 support: Yes

Internet speed test: Yes

HbbTV: Yes

AUDIO

Clear language from ARD: Yes via DVB

CONNECTIONS

HDMI™ (out): 1

USB: 2 (USB 2.0)

Common Interface Plus (CI+): Yes

Digital electric audio output (S/PDIF): Yes

F socket: 2

Connector for external IR-Receiver: 1

Ethernet 1Gbit/s (RJ-45): 1

DC IN: 1

DECODER

Video decoder: MPEG-2 MP@HL/ML, H.264/MPEG-4 AVC

Audio decoder: MPEG-1 & MPEG-2 Layer I, II, III

DECRYPTION SYSTEM

CI+: Yes

DISPLAY

Picture in Picture (PIP): Yes (2x HD, 2x SD, 1x SD u. 1x HD)

Picture and Picture (PAP): Yes

Freeze frame: Yes

Zoom: Yes

SD: Yes

HD: Yes

1080p: Yes

1080i: Yes

720p: Yes

576p: Yes

576i: Yes

Type: 7-segments, 4-digits, white

HANDLING/COMFORT

Page memory: 1.000

Teletext subtitles: Yes

Media Player: Yes

Selection regional channels: Yes

Ideal for camping: Yes

Hotel mode: Yes

Autostandby: Yes

Clock: Yes

Alarm: Yes

Channel presets: 9.999

Sleep timer: Yes

Remote control: Yes

Teletext: Yes

HOTEL MODE

Protected access to hotel mode: Yes

Customisable start screen: Yes

Lockable volume: Yes

Menu locking: Yes

Control panel lock: Yes

Integrated LED clock: Yes

Selectable start source: Yes

Selectable start channel: Yes

NETWORK & COMMUNICATION

1000Base-T: Yes

IPv4: Yes

TCP/IP: Yes

HTTPS: Yes

HTTP: Yes

UPnP: Yes

IGMP: Yes

UDP: Yes

RTP: Yes

DHCP: Yes

OTHER FEATURES

OSD languages: English, Portuguese, French, German, Russian, Czech, Polish, Greek, Turkish, Italian, Swedish, Spanish, Dutch, Hungarian

POWER CONSUMPTION

Standby LED: 0,4 W

In operation: 17,1 W

POWER SUPPLY

Nominal voltage: 230 V

Frequency: 50 Hz

Mains adapter: external DC12V/3A

STREAMING
DLNA Client: Yes
DLNA Server: Yes
Cloud store: Ja
Parental Control: Yes

SUPPORTED FORMATS & CODECS
Video-Codecs: MPEG-2, MPEG-4, MPEG-1, H.264 (up to H.264/AVC Level 4.2)
Video-Formats: M4V, MP4, MKV, MOV, MPG, MTS, TS, TS4, VOB, M2TS, AVI, ASF
Picture-Formats: BMP, JPEG, GIF, PNG
Audio-Formats: WAV, MP3, AAC, FLAC, M4A, MP2, DDAC3, AIFF

TUNER
Tuner type: Twin-Tuner
DVB-S tuner: 2
Single Cable Solution (SatCR): SCR1 = EN50494, SCR2 = EN50607
Satellite radio: Yes
Internet radio: Yes
Reception on: HD-TV, SD-TV
TECHNISELECT 12 ready: Yes
TECHNIROUTER ready: Yes
DVB-IP (multicast): 1

TUNER - SAT
Reception range: 950 ... 2.150 MHz
Viterbi rates: 1/2, 2/3, 3/4, 5/6, 7/8 , (auto)
DVB-S: QPSK
DVB-S: 2 ... 45
DVB-S2: 8PSK-QPSK
DVB-S2: 10 ... 31
FEC: RS, LDPC, BCH

SCOPE OF DELIVERY
DIGIT ISIO S4, remote control TechniControl including batteries, power supply, HDMI cable, manual, warranty card

Test Results DIGIT ISIO S4



SATVISION 07/2023