



## Passive Splitter 5P2

2-way splitter for 1 orbit position

| EAN           | Colour        | Item no.  | Weight (Box) | Weight | Device (W x H x D) | Box                |
|---------------|---------------|-----------|--------------|--------|--------------------|--------------------|
| 4019588132429 | silver/yellow | 0001/3242 | 438 g        | 392 g  | 12,6 x 13,5 x 3 cm | 16 x 14,5 x 3,8 cm |

### TOP FEATURES

Distributes Sat signal into 2 routes with only 4 dB attenuation

#### AMBIENT OPERATING CONDITIONS

Ambient temperature: -20 50 °C

#### AMPLIFICATION

Sat: -4 dB

Terrestrial: -4 dB

#### POWER SUPPLY

Type of power supply: internal

Frequency: 50 / 60 Hz

Nominal voltage: 230 V

LNB voltage supply: 14 18 V

#### PREPARED FOR

Number of orbit positions: 1

#### RECEPTION RANGE

Sat: 950 ... 2.400 MHz

Terrestrial: 5 ... 862 MHz

#### TECHNICAL DATA

Satellite inputs: 4

Terrestrial input: 1

Distribution length: 100 m

#### TRANSMISSION LOSS

Sat: 4 dB

Terrestrial: 4 dB

#### SCOPE OF DELIVERY