



STEERINGMUX 8

VHF/UHF antenna diplexer for DVB-T2

EAN	Item no.
4019588060340	0000/6034

<p>AMBIENT OPERATING CONDITIONS</p> <p>Ambient temperature: -10 ... 55 °C</p> <p>IP class: 53</p> <p>Humidity: 10 ... 75 %</p>	<p>AMPLIFICATION</p> <p>UKW: 30 dB</p> <p>VHF I: 30 dB</p> <p>VHF III: 30 dB</p> <p>UHF: 34 dB</p>	<p>GENERAL CHARACTERISTICS</p> <p>Top features: Four signal inputs 2 x UHF, VHF, FM/DAB+</p> <p>Top features: One signal output directly to TV or decoder</p> <p>Top features: DC pass 60 mA</p> <p>Top features: Channels: VHF/FM, VHF: 6-12, UHF: 21-60</p> <p>Top features: IP 53 class</p> <p>Top features: Waterproof housing</p>
<p>POWER SUPPLY</p> <p>Mains adapter: internal</p> <p>Nominal voltage: 230 V ~</p> <p>Frequency: 50 Hz</p> <p>Effective output: 7 W</p>	<p>RECEPTION RANGE</p> <p>UKW: 87,5 ... 108 MHz</p> <p>VHF III E5-E12: 174 ... 230 MHz</p> <p>UHF E21-E69: 470 ... 790 MHz</p>	<p>TECHNICAL DATA</p> <p>Input: 4</p> <p>Connector type: F</p> <p>Impedance: 75 Ω</p> <p>Output level: 115</p> <p>Level attenuation: 20 dB every input</p>

<p>SCOPE OF DELIVERY</p> <p>STEERINGMUX 8 crossover, protective housing, clamp for mounting e.g. on an antenna mast, operating instructions</p>
--