



TECHNIROUTER MINI 2/1x2

Expand an existing cable derivation into a Twin solution or into a two-subscriber solution without laying additional cables

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588032897	silver/yellow	0000/3289	400 g	200 g	5 x 2,8 x 11,5 cm	18 x 4 x 18,5 cm

FILTER-NAVIGATION

Number participants: 2

AMBIENT OPERATING CONDITIONS

Humidity: 10 ... 75 %

Ambient temperature: -25 ... 55 °C

AMPLIFICATION

Sat: 2 dB

Terrestrial: -3 dB

DECOUPLING

Trunks: 30 dB

GENERAL CHARACTERISTICS

Top features: Expansion of coaxial line to twin function

Top features: No additional cable routing required

Top features: 2 adjustable orbit positions

Top features: Very compact dimensions

Top features: Can be connected behind Twin, Quatro Switch LNB and multiswitch

Top features: Terrestrial outlet for DVB-T(2)/UHV

POWER CONSUMPTION

In operation: max. 2 W (Standby 0 W)

POWER SUPPLY

Mains adapter: extenal 12 VDC/1,5 A

Frequency: 50 Hz

Nominal voltage: 230 V

RECEPTION RANGE

Sat: 950 ... 2.150 MHz

Terrestrial: 47 ... 862 MHz

SINGLE-CABLE OUTPUT

Output frequency: 47 ... 2.150 MHz

Number of output channels: 2

Frequency of the output channels: 1284, 1400 MHz

Frequency SAT: 1.250 ... 1.430 MHz

Frequency DVB-T: 47 ... 862 MHz

Output level: - 3 dB

TECHNICAL DATA

Satellite inputs: 2

Number of cable connections: 1

Subscribers per cable: 2

SCOPE OF DELIVERY

TechniRouter Mini 2/1x2, Manual

Test Results TECHNIROUTER MINI 2/1x2



SAT Empfang (02/2012)



Satvision (10/2012)