



## TECHNIROUTER MINI 2/1x2

Expand an existing cable derivation into a Twin solution or into a two-subscriber solution without laying additional cables

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588032897	silver/yellow	0000/3289	400 g	200 g	5 x 2,8 x 11,5 cm	18 x 4 x 18,5 cm

### TOP FEATURES

- Twin reception or supplying two satellite receivers with only one cable. Router for expanding an existing cable branch into a twin or two-subscriber solution without laying new cables
- The PIN code technology of the single-cable solution enables access protection on compatible receivers. Power is supplied via the receiver/TV. Quality Made in Germany
- The TechniRouter Mini 2/1x2 uses Satellite Channel Router (SCR) technology. The connected satellite receivers or TV sets with integrated satellite tuner must support the EN 50494 standard
- The router can only be connected to two existing free subscriber lines of a multiswitch or a twin or quad switch LNB. It is not suitable for Quattro LNB

### SONSTIGES

bf\_filter\_number\_of\_participants: 2

### AMBIENT OPERATING CONDITIONS

Humidity: 10 ... 75 %

Ambient temperature: -25 ... 55 °C

### AMPLIFICATION

Sat: 2 dB

Terrestrial: -3 dB

## DECOUPLING

Trunks: 30 dB

## GENERAL CHARACTERISTICS

Top features: Expansion of coaxial line to twin function  
Top features: No additional cable routing required  
Top features: 2 adjustable orbit positions  
Top features: Very compact dimensions  
Top features: Can be connected behind Twin, Quattro Switch LNB and multiswitch  
Top features: Terrestrial outlet for DVB-T(2)/UHV

## POWER CONSUMPTION

In operation: max. 2 W (Standby 0 W)

## POWER SUPPLY

Mains adapter: external 12 VDC/1,5 A

Frequency: 50 Hz

Nominal voltage: 230 V

## RECEPTION RANGE

Sat: 950 ... 2.150 MHz

Terrestrial: 47 ... 862 MHz

## SINGLE-CABLE OUTPUT

Output frequency: 47 ... 2.150 MHz

Number of output channels: 2

Frequency of the output channels: 1284, 1400 MHz

Frequency SAT: 1.250 ... 1.430 MHz

Frequency DVB-T: 47 ... 862 MHz

Output level: - 3 dB

## TECHNICAL DATA

Satellite inputs: 2

Number of cable connections: 1

Subscribers per cable: 2

## SCOPE OF DELIVERY

TechniRouter Mini 2/1x2, Manual

## Test Results TECHNIROUTER MINI 2/1x2



SAT Empfang (02/2012)

Satvision (10/2012)