



TECHNISWITCH 5/8 K

Multi-switch system with connection possibility of 4 levels for distribution to up to 24 participants

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588032583	blue/yellow	0000/3258	374 g	374 g	17,1 x 12,6 x 3,32 cm	17,5 x 18,5 x 3,9 cm

AMBIENT OPERATING CONDITIONS

Ambient temperature: -25 ... 55 °C

AMPLIFICATION

Sat: -4 ... -2 dB

Terrestrial: 1 ... 4 dB

DECOUPLING

Output: > 35 dB

GENERAL CHARACTERISTICS

Top Features: For distribution of one satellite position

Top Features: Up to 24 subscribers can be connected

Top Features: For connecting a Quatro LNB

Top Features: Up to 100 m distribution length due to inclination compensation

Top Features: Energy saving - no mains adapter for operation

Top features: No attenuation in satellite range

RECEPTION RANGE

Sat: 950 ... 2.150 MHz

Terrestrial: 47 ... 862 MHz

TECHNICAL DATA

Satellite inputs: 4

Terrestrial input: 1

Outputs: 8

Distribution length: max. 100 m

TRANSMISSION LOSS

Sat: 2 ... 5 dB

Terrestrial: 2 ... 3 dB

SCOPE OF DELIVERY

TechniSwitch 5/8 K, manual