



## TECHNISYSTEM 5/8 K

Multi-switch system with connection possibility of 4 ZF levels for distribution to up to 8 participants

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588032484	blue/yellow	0000/3248	400 g	400 g	17,1 x 10,13 x 3,3 cm	17,6 x 18,6 x 4 cm

### TOP FEATURES

- Made in Germany; cascade module for professional multiswitch systems for implementing larger cable networks in residential units, complexes, and large facilities
- The professional system for Quattro LNBs features 4 satellite inputs, 1 terrestrial input, and 8 outputs
- No attenuation in the satellite band, with tilt compensation
- Attention: The components of the TECHNISYSTEM are not compatible with TECHNISWITCH components

### AMBIENT OPERATING CONDITIONS

Ambient temperature: -25 ... 55 °C

### AMPLIFICATION

Sat: -2 ... 3 dB

### DECOUPLING

Output: > 35 dB

### GENERAL CHARACTERISTICS

Top features: No attenuation in satellite range

Top features: Tilt gain

Top features: For quad LNB

### RECEPTION RANGE

Sat: 950 ... 2.150 MHz

Terrestrial: 47 ... 862 MHz

### TECHNICAL DATA

Satellite inputs: 4

Terrestrial input: 1

Outputs: 8

Distribution length: 100 m

**TRANSMISSION LOSS**

Sat: 2 ... 5 dB

Terrestrial: 2 ... 3 dB

**SCOPE OF DELIVERY**

TechniSystem 5/8 K, Bedienungsanleitung