



DIGICORDER ISIO S1

Digital HDTV satellite receiver with internet functionality

Hard drive	EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
500 GigaByte	4019588517264	silver	0501/4726	3,3 kg	2,9 kg	43,5 x 6 x 19,9 cm	49 x 16 x 26 cm
500 GigaByte	4019588507265	black	0500/4726	3,3 kg	2,9 kg	43,5 x 6 x 19,9 cm	49 x 16 x 26 cm
1.000 GigaByte	4019588117266	silver	1001/4726	3,3 kg	2,9 kg	43,5 x 6 x 19,9 cm	49 x 16 x 26 cm
1.000 GigaByte	4019588107267	black	1000/4726	3,3 kg	2,9 kg	43,5 x 6 x 19,9 cm	49 x 16 x 26 cm

TOP FEATURES

UPnP/DLNA/Client- & Server function for home networking

IP module for access to libraries, Video on demand services and apps

2 CI + interface (compatible with HD and Sky +)

Integrated hard drive (1 TB)

free browsing, and HbbTV ISIO Live! (TechniSat Service Portal)

HDTV Twin Tuner

AMBIENT OPERATING CONDITIONS

Humidity: 10 ... 75 %

Ambient temperature: 5 ... 35 °C

LNB CONTROL

Vertical: 14 V

Horizontal: 18 V

Band switch: 22 kHz

Current consumption: max. 400 mA (kurzschlussfest)

DiSEqC: 1.0 / 1.2

TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL: Yes

INTERNET/NETWORK

HTML 5 support: Yes

HbbTV: Yes

CARD READER

SD card: Yes

CONNECTIONS

HDMI™ (out): 1

Digital electric audio output (S/PDIF): Yes

Digital optical audio out: Yes

Audio out analogue (RCA): Yes (rechts / links)

YUV (component output): 1

Scart: 1

Video Cinch out: 1

Ethernet 10/100 (RJ-45): Yes

F socket: 2

DECRYPTION SYSTEM

Conax: Yes

CI+: Yes

DISPLAY

Picture in Picture (PIP): Yes (2 x SD, 1 x SD u. 1 x HD)

Freeze frame: Yes

Zoom: Yes

576i: Yes

576p: Yes

SD: Yes

HD: Yes

720p: Yes

1080i: Yes

HANDLING/COMFORT

Sleep timer: Yes

Alarm: Yes

HOTEL MODE

Protected access to hotel mode: Yes

Customisable start screen: Yes

Lockable volume: Yes

Menu locking: Yes

Control panel lock: Yes

Integrated LED clock: Yes

Selectable start source: Yes

Selectable start channel: Yes

OTHER FEATURES

OSD languages: English, German, French, Greek, Italian, Dutch, Polish, Portuguese, Russian, Swedish, Spanish, Czech, Turkish, Hungarian

Total programme memory: 5.000

Regional channel selection: Yes

POWER CONSUMPTION

Standby fast start: 6,9 W

Standby LED: 0,25 W

In operation: 13 W

POWER SUPPLY

Nominal voltage: 230 V

Frequency: 50 Hz

Mains adapter: internal

SUPPORTED FORMATS & CODECS

Video-CODECS: MPEG-2, MPEG-4, MPEG-1, H.264, DivX

Video-Formats: MKV, MP4, MOV, TS, TS4, VOB, WMV, Xvid, AVI

JPEG: Yes

Audio-Formats: AAC, MP3, M4A, MP2

TUNER

Tuner type: DigitalSat

DVB-S tuner: 2

Single Cable Solution (SatCR): SCR1 = EN50494

Reception on: HDTV (MPEG-4 & 2), SD (MPEG-2)

Input impedance: 75 Ω

TECHNIROUTER ready: Yes

TECHNISELECT 12 ready: Yes

TUNER - SAT

Reception range: 950 ... 2.150 MHz

Viterbi rates: 1/2, 2/3, 3/4, 5/6, 7/8 , (autom. Anpassung)

DVB-S: QPSK

DVB-S: 2 ... 45

DVB-S2: 8PSK-QPSK

DVB-S2: 10 ... 31

FEC: Viterbi and Reed-Solomon

SCOPE OF DELIVERY

DigiCorder ISIO S1, remote control including batteries, mains cable, HDMI cable, operating instructions, guarantee card

Test Results DIGICORDER ISIO S1



Note: Gut (78,6 von 100
Punkten)
sat+kabel (07-08/2011)

SFT (01/2012)