



TECHNIROUTER 5/2x4 K

Digital single-cablesolution for the distribution of satellite signals from one orbital position via two cable harnesses for an existing cable structure

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588032934	blue/yellow	0000/3293	400 g	300 g	14 x 13 x 3,2 cm	24,5 x 13,5 x 5,5 cm

AMBIENT OPERATING CONDITIONS

Humidity: 10 ... 75 %

Ambient temperature: -25 ... 55 °C

RECEPTION RANGE

Terrestrial: 47 ... 862 MHz

Sat: 950 ... 2.150 MHz

TRANSMISSION LOSS

Sat: 3 ... 5 dB

Terrestrial: 2 ... 3 dB

AMPLIFICATION

Sat: 17 ... 22 dB

Terrestrial: -12 dB

SINGLE-CABLE OUTPUT

Output frequency: 47 ... 2.150 MHz

Number of output channels: 2 x 4

Frequency of the output channels: 1284, 1400, 1516, 1632 MHz

Frequency SAT: 950 ... 2.150 MHz

Frequency DVB-T: 47 ... 862 MHz

TUNER

TECHNIROUTER ready: Yes

DECOUPLING

Trunks: 45 dB

TECHNICAL DATA

Satellite inputs: 4

Terrestrial input: 1

Number of cable connections: 2

Subscribers per cable: maximal 4

SCOPE OF DELIVERY

TechniRouter 5/2x4 K, Bedienungsanleitung