



## 2 way satellite splitter

for the 2-fold distribution or merger of Sat signals

EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588132207	0001/3220	34 g	27 g	5,4 x 4,6 x 1,5 cm	5,2 x 5,8 x 1,8 cm

### TOP FEATURES

DC power pass

DC-diodenentkoppelt

DiSEqC-compatible

TECHNIROUTER-compatible

### DECOUPLING

5 - 862 MHz: Typ. 16 dB (< 40 MHz = 8 dB)

950 - 1750 MHz: Typ. 16 dB

1750 - 2150 MHz: Typ. 15 dB

### RETURN LOSS

5 - 862 MHz: Typ. 16 dB

950 - 1750 MHz: Typ. 12 dB

1750 - 2150 MHz: Typ. 12 dB

### TECHNICAL DATA

Input: 1

Outputs: 2

Frequency range: 5 ... 2.150 MHz

Shielding factor:  $\geq 75$  dB EN 50083-2 (Class A)

Connector type: F female

Impedance: 75  $\Omega$

### TRANSMISSION LOSS

5 - 862 MHz: Typ. 4 dB ( $\pm 1$ )

950 - 1750 MHz: Typ. 5 dB ( $\pm 1$ )

1750 - 2150 MHz: Typ. 6 dB ( $\pm 1,5$ )

### SCOPE OF DELIVERY

2-Wege Sat-Verteiler