



HD-T 225

DVB-T2 HD Receiver

Colour	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
Schwarz	4019588048409	0000/4840	427 g	112 g	12 x 3 x 8 cm	19,7 x 6 x 11,2 cm

TOP FEATURES

- The digital DVB-T2 HD receiver receives unencrypted TV programmes via antenna using modern HEVC H265 technology. Its compact size allows for flexible placement in the living room, bedroom or kitchen.
- With HDMI and SCART, the receiver is suitable for both modern and older TV sets. Thanks to its 12V power supply, the lightweight box is also ideal for mobile use in motorhomes or when camping.
- USB media player: Videos, music and images stored on a hard drive or stick connected to the receiver can be easily played back using the box's integrated media player.
- Timeshift: After connecting an external USB storage device, you can manually pause a programme that is currently being broadcast and continue watching it at a later time. Recording and saving programmes is not supported.

SONSTIGES

bf_filter_empfangsart: DVB-T2

CONNECTIONS

HDMI™ (out): 1

USB: 1 (USB 2.0)

Scart: 1

IEC-Connector: Yes (IEC 60169-2, Female, 75Ohm nominal)

DC IN: 1

DECODER

Video decoder: HEVC/H.265: Main Profile@4.1 and Main10 Profile@L4.1; H.264: BP/MP&HP@L3/L4.1/L4.2; MPEG2: MP@ML/HL; MPEG4: SP@L0-3, ASP@L0-5;

Audio decoder: MPEG 1/2 Layer I/II/III, MPEG 2/4 LC-AAC, MPEG-4 HE-AAC@Level 4, Dolby Digital AC-3, Dolby Digital Plus EAC-3

DISPLAY

SD: Yes

HD: Yes

1080p: Yes

1080i: Yes

720p: Yes

576p: Yes

576i: Yes

480p: Yes

480i: Yes

HANDLING/COMFORT

Electronic Program Guide (EPG): Ja

Teletext: Yes

OTHER FEATURES

OSD languages: German, English

PICTURE-FORMATS

Picture-Formats: 576i, 576p, 720p, 1080i, 1080p, 480i, 480p

POWER CONSUMPTION

Standby LED: < 0,3 W

In operation: 4,7 W

POWER SUPPLY

Mains adapter: external DC 12 V / 1,0 A

Nominal voltage: 230 V

Frequency: 50 Hz

TUNER

Tuner type: Single-Tuner

Tuner DVB-T2: DVB-T2/HEVC (H.265)

DVB-T Tuner: 1

Reception on: HDTV (H.265, H.264), SD (MPEG-2)

TUNER - TERRESTRIAL

Reception range 1: 174 ... 230 MHz

Reception range 2: 470 ... 862 MHz

Demodulation: QPSK, 16 QAM, 64QAM, 256QAM

Transmission mode: 1k, 2k, 4k, 8k, 16k, 32k

SCOPE OF DELIVERY

HD-T 225, remote control incl. batteries, HDMI cable, power supply, manual