

UNYSAT Universal-Twin-LNB

Digital-LNB for two participants

Colour	EAN	Item no.	Weight (Box)	Weight
grey	4019588108387	0010/8382	420 g	366 g

TOP FEATURES

- For 2 participant
- Special weatherproof housing for the excellent receiving electronics
- Suitable for all TechniSat SATMAN dishes
- Quick and easy assembly without a retaining clamp
- LTE interference-safe

LOCAL OSCILLATOR

- Low band: 9,75 GHz
- High band: 10,6 GHz
- Accuracy: ± 1 MHz
- Temperature drift: ± 0,5 MHz
- Phase noise: -75 @10kHz

LNB CONTROL

- Band switch: 22 kHz
- Vertical: 11,5 ... 14,5 V
- Horizontal: 16 ... 19 V

AMBIENT OPERATING CONDITIONS

- Ambient temperature: -40 ... 70 °C
- Humidity: 10 ... 95 %

INPUT FREQUENCY RANGE

- Low band: 10,7 ... 11,7 GHz
- High band: 11,7 ... 12,75 GHz

NOISE FACTOR

- Noise figure: typ. 0,9 dB

OUTPUT FREQUENCY RANGE

- Low band: 950 ... 1.950 MHz
- High band: 1.100 ... 2.150 MHz

POWER SUPPLY

Power consumption: max. 140 mA

PREPARED FOR

Number of orbit positions: 1

Number of clients: 2

TECHNICAL DATA

Outputs: 2

Skew: -20 ... 20 °

Impedance: 75 Ω

Amplification: 58 ... 64 dB

Feed reception: For SATMAN mm

Connector type: F female

SCOPE OF DELIVERY

UNYSAT Universal-Twin-LNB, Montageanleitung