



Universal-V/H-LNB

Digital LNB for two-subscriber reception

EAN	Colour	Item no.
4019588208940	black	0020/8194

TOP FEATURES

Feed ø 40 mm

Feed ø 40 mm

LOCAL OSCILLATOR

Low band: 9,75 GHz ± 3MHz

High band: 10,6 GHz ± 3MHz

LNB CONTROL

Vertical: 12 ... 14,5 V

Horizontal: 16 ... 20 V

AMBIENT OPERATING CONDITIONS

Ambient temperature: -40 ... 70 °C

Humidity: 10 ... 95 %

INPUT FREQUENCY RANGE

Low band: 10,7 - 11,7 GHz

High band: 11,7 - 12,75 GHz

NOISE FACTOR

Lower frequency range: 0,7 dB max.

Upper frequency range: 0,7 dB max.

OUTPUT FREQUENCY RANGE

Low band: 950 - 1.950 MHz

High band: 1.100 - 2.150 MHz

POWER SUPPLY

LNB voltage supply: 12 ... 20 V

Power consumption: max. 150 mA

PREPARED FOR

Number of clients: 1

Number of orbit positions: 1

TECHNICAL DATA

Outputs: 1

Feed reception: 40 mm

Impedance: 75 Ω

Connector type: F female

SCOPE OF DELIVERY

Universal-V/H-LNB