



## F-type compression connector 7.0

Compression F connector for 7mm cable

| EAN           | Item no.  | Weight (Box) | Weight |
|---------------|-----------|--------------|--------|
| 4019588133518 | 0001/3351 | 24 g         | 6 g    |

### TOP FEATURES

High-end F connector

100% waterproof

Operational up to 3 GHz

Without inner sleeve - simplified assembly

Suitable for many RG6 coaxial cables

Assembly with compression pliers 0000/3339 from TechniSat

### ATTENUATION

10 MHz: 0,02

100 MHz: 0,02

450 MHz: 0,03

800 MHz: 0,05

862 MHz: 0,04

1000 MHz: 0,06

1350 MHz: 0,11

2250 MHz: 0,11

### RETURN LOSS

65 - 470 MHz:  $\geq 34$  dB

470 - 1800 MHz:  $\geq 33$  dB

1800 - 2450MHz:  $\geq 33$  dB

### SHIELDING

30 - 1000 MHz:  $> 105$  dB CoMeT

1000 - 2250 MHz:  $> 95$  dB CoMeT

### TECHNICAL DATA

Protection class: IPX8

Impedance: 75  $\Omega$

Diameter dielectric: max. 4,6 mm

Diameter with coating: 6,8 ... 7 mm

### TRANSFER IMPEDANCE

5MHz:  $< 5$

30 MHz:  $< 2,5$

### SCOPE OF DELIVERY

Pack: 100 piece