



TECHNIBOX K1 CSP

HDTV cable Set-top-box with integrated Conax-Chip-Set-Pairing

EAN	Colour	Item no.
4019588047761	black	0000/4776

TOP FEATURES

HDTV cable tuner (DVB-C)	Conax decryption with chipset pairing	Electronic program guide (EPG)
Multimedia playback via USB (MP3, JPEG, etc.)	Operation on 12V	Easy start-up via AutoInstall
ISIPRO: automatic updates of the programme list		

AMBIENT OPERATING CONDITIONS

Humidity: 10 ... 75 %
Ambient temperature: 5 ... 35 °C

TECHNISAT ADDED VALUE SERVICES

ISIPRO cable: Yes
AUTOINSTALL: Yes

CONNECTIONS

HDMI™ (out): 1
USB: 1 (USB 2.0)
Smartcard reader: Yes
Digital electric audio output (S/PDIF): Yes
Scart: 1
IEC-Connector: Yes
Connector for external IR-Receiver: 1

DECRYPTION SYSTEM

Conax: Yes
Conax CSP: Yes Ab Software 2.46.04-2206d

DISPLAY

Freeze frame: Yes
SD: Yes
HD: Yes
1080i: Yes
720p: Yes
576p: Yes
576i: Yes

HANDLING/COMFORT

Teletext subtitles: Yes
Alarm: Yes
Ideal for camping: Yes
Teletext: Yes
Sleep timer: Yes

OTHER FEATURES

OSD languages: English, German, French, Italian, Dutch, Polish, Portuguese, Russian, Swedish, Spanish, Czech, Turkish, Hungarian
Total programme memory: 4.000

POWER CONSUMPTION

Standby fast start: < 3 W
Standby LED: < 0,3 W
In operation: 7,5 W

POWER SUPPLY

Mains adapter: external DC 12V/1,5A
Nominal voltage: 230 V
Frequency: 50 Hz

READY FOR RECEPTION

M7: Yes

SUPPORTED FORMATS & CODECS

Video-Codecs: MPEG-2, MPEG-4, MPEG-1, H.264

Video-Formats: TS4, TS, VOB

Picture-Formats: BMP, JPEG, PNG

Audio-Formats: MP2, MP3

TUNER

Tuner type: DigitalCable

DVB-C Tuner: 1

Reception on: HD-TV, SD-TV, radio

TUNER - CABLE

Reception range: 47 ... 862 MHz

Demodulation: 16 / 32 / 64 / 128 / 256 QAM

Symbol rate: 1 ... 7

FEC: Reed-Solomon (204, 188)

SCOPE OF DELIVERY

TECHNIBOX K1 CSP, remote control (incl. batteries), external power supply, antenna cable, manual