



TECHNISELECT 12

For feeding 12 selectable satellite transponders into a single cable distribution system

| EAN | Colour | Item no. | Weight (Box) | Weight | Device (W x H x D) | Box |
|---------------|-------------|-----------|--------------|--------|----------------------|--------------------|
| 4019588032996 | blue/yellow | 0000/3299 | 800 g | 500 g | 29,2 x 11,2 x 3,1 cm | 31,8 x 20 x 4,5 cm |

LNB CONTROL

Vertical: 13 V über VL

Current consumption: max. 400 mA (für LNB und / oder Verstärker)

GENERAL CHARACTERISTICS

Top features: Einspeisung von digitalen Sat-Signalen in vorhandene Kabelstrukturen

Top features: Eingang zum Empfang von Terrestrischen Signalen

Top features: 4 vollwertige Receiverausgänge oder Sat-Stämme

Top features: Messausgang -20 dB

Top features: Stromsparfunktion

AMBIENT OPERATING CONDITIONS

Humidity: 10 ... 75 %

Ambient temperature: -25 ... 55 °C

POWER CONSUMPTION

In operation: 11 W (inkl. LNB)

DECOUPLING

Trunks: 30 dB

POWER SUPPLY

Frequency: 50 Hz

Nominal voltage: 230 V

Mains adapter: internal

RECEPTION RANGE

Sat: 950 ... 2.150 MHz

Terrestrial: 80 ... 790 MHz

SINGLE-CABLE OUTPUT

Output frequency: 80 ... 2.150 MHz

Number of output channels: 12

Frequency of the output channels: 974, 1076, 1178, 1280, 1382, 1484, 1586, 1688, 1790, 1892, 1994, 2096 MHz

Frequency SAT: 950 ... 2.150 MHz

Frequency DVB-T: 80 ... 790 MHz

Output level: max. 105

Output level: 12 ... 20 dB (Einstellbare Verstärkung)

TECHNICAL DATA

Satellite inputs: 4

Terrestrial input: 1

Number of cable connections: 1

Subscribers per cable: über 50

TRANSMISSION LOSS

Terrestrial: -20 ... -12 dB (Einstellbare Verstärkung)

SCOPE OF DELIVERY

TechniSelect 12, manual, CD-ROM with TechniSelect Configuration Tool, USB-cable

Test Results TECHNISELECT 12



Infosat (02/2012)



Infosat (02/2012)