

TECHNIPRO RV 600-14E

Satellite pass-through socket for single-cable systems. Antenna socket with 14 dB isolation attenuation and electronic overload protection.

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588031845	silver	0000/3184	102 g	100 g	7 x 7 x 2,5 cm	10 x 12,5 x 1 cm
4019588031845	silver	0000/3184	102 g	100 g	7 x 7 x 2,5 cm	10 x 12,5 x 1 cm

CONNECTOR TYPE
Radio: IEC connector (f)
TV: IEC connector (m)
SAT: F-socket

FREQUENCY RANGE
Radio: 87,5 ... 108 MHz
SAT: 950 ... 2.150 MHz
TV: 47...68/ 118 ... 862 MHz

SHIELDING FACTOR
47 - 300 MHz: ≥ 85 dB
300 - 470 MHz: ≥ 80 dB
470 - 950 MHz: ≥ 75 dB
950 - 2150 MHz: ≥ 55 dB

TAP LOSS
Radio: 15 dB
SAT: 14 dB
TV: 14 dB

TRANSMISSION LOSS
VHF: 0,7 dB
UHF: 0,8 dB
Sat: 1,5 dB

SCOPE OF DELIVERY
TechniPro RV 600-14E