



TECHNIPRO RV 600-14E

Satellite pass-through socket for single-cable systems. Antenna socket with 14 dB isolation attenuation and electronic overload protection.

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588031845	silver	0000/3184	102 g	100 g	7 x 7 x 2,5 cm	10 x 12,5 x 1 cm
4019588031845	silver	0000/3184	102 g	100 g	7 x 7 x 2,5 cm	10 x 12,5 x 1 cm

CONNECTOR TYPE	FREQUENCY RANGE	SHIELDING FACTOR
Radio: IEC connector (f)	Radio: 87,5 ... 108 MHz	47 - 300 MHz: ≥ 85 dB
TV: IEC connector (m)	SAT: 950 ... 2.150 MHz	300 - 470 MHz: ≥ 80 dB
SAT: F-socket	TV: 47...68/ 118 ... 862 MHz	470 - 950 MHz: ≥ 75 dB
		950 - 2150 MHz: ≥ 55 dB
TAP LOSS	TRANSMISSION LOSS	SCOPE OF DELIVERY
Radio: 15 dB	VHF: 0,7 dB	TechniPro RV 600-14E
SAT: 14 dB	UHF: 0,8 dB	
TV: 14 dB	Sat: 1,5 dB	