



TECHNIPRO RV 600-13

Sat-transfer socket with 13 dB insertion loss for loop through-systems in one cable solutions for flush mounting with frame and cover

| EAN | Colour | Item no. | Weight (Box) | Weight | Device (W x H x D) | Box |
|---------------|--------|-----------|--------------|--------|--------------------|--------------|
| 4019588031814 | white | 0000/3181 | 200 g | 100 g | 7,8 x 7,8 x 4 cm | 8 x 8 x 5 cm |

CONNECTOR TYPE

Radio: IEC connector (f)

TV: IEC connector (m)

SAT: F-socket

FREQUENCY RANGE

Radio: 5 ... 139 MHz

SAT: 950 ... 2.150 MHz

TV: 5 ... 860 MHz

SHIELDING FACTOR

47 - 300 MHz: 75 dB

300 - 470 MHz: 75 dB

470 - 950 MHz: 65 dB

950 - 2150 MHz: 55 dB

TAP LOSS

Radio: typ. 18 dB

SAT: typ. 13 dB

TV: typ. 15 dB

TRANSMISSION LOSS

VHF: 1,8 dB

UHF: 2,3 dB

Sat: typ. 3,3 dB

SCOPE OF DELIVERY

TechniPro RV 600-13, housing for surface mounting, cover