

F Compression connector 4.9

Premium 4.9 F connector in compression design with shielding values of ≥ 120 dB

EAN	Colour	Item no.
4019588100374	silver	0100/3337

TOP FEATURES

- High-end F connector
- 100% waterproof
- Operational up to 3 GHz
- Suitable for COAXSAT 120-4.6 and 140-4.6 cables from TechniSat
- Suitable for all RG6 coaxial cables 1.0/4.6
- Installation with compression pliers 0000/3339 from TechniSat

ATTENUATION

- 10 MHz: 0,01
- 100 MHz: 0,01
- 450 MHz: 0,01
- 800 MHz: 0,05
- 862 MHz: 0,01
- 1000 MHz: 0,02
- 2250 MHz: 0,02

RETURN LOSS

- 65 - 470 MHz: ≥ 38 dB
- 470 - 1800 MHz: ≥ 38 dB
- 1800 - 2450MHz: ≥ 35 dB

SHIELDING

- 30 - 1000 MHz: > 140 dB CoMeT
- 1000 - 2250 MHz: > 120 dB CoMeT

TECHNICAL DATA

- Protection class: IPX8
- Impedance: 75 Ω
- Diameter dielectric: max. 4,6 mm
- Diameter with coating: 6,8 ... 7 mm

TRANSFER IMPEDANCE

- 5MHz: < 2,5
- 30 MHz: < 2,5

SCOPE OF DELIVERY

- Pack: 100 piece