



F Compression connector 3.9

Premium 3.9 F connector in compression design with shielding values ≥ 118 dB

EAN	Colour	Item no.	Weight (Box)	Weight
4019588133495	silver	0001/3349	1,24 kg	1,22 kg

TOP FEATURES

High-end F connector

100% waterproof

Operational up to 3 GHz

Suitable for all TechniSat COAXSAT 115 cables

Suitable for all coaxial cables 0.8/3.6

Installation with compression pliers 0000/3339 from TechniSat

ATTENUATION

10 MHz: 0,01

100 MHz: 0,01

450 MHz: 0,01

800 MHz: 0,05

862 MHz: 0,01

1000 MHz: 0,02

2250 MHz: 0,02

RETURN LOSS

65 - 470 MHz: ≥ 28 dB

470 - 1800 MHz: ≥ 26 dB

1800 - 2450MHz: ≥ 26 dB

SHIELDING

30 - 1000 MHz: > 125 dB CoMeT

1000 - 2250 MHz: > 118 dB CoMeT

TECHNICAL DATA

Protection class: IPX8

Impedance: 75Ω

Diameter dielectric: max. 3,6 mm

Diameter with coating: 5,6 ... 5,8 mm

TRANSFER IMPEDANCE

5MHz: $< 2,5$

30 MHz: $< 2,5$

SCOPE OF DELIVERY

Pack: 100 piece