



TECHNISWITCH 5/8 Mini

Compact multiswitch for distribution of 4 IF levels and terrestrial signals for 8 participants.

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588032606	blue/yellow	0000/3260	200 g	160 g	7,9 x 3,3 x 11,5 cm	9,5 x 4 x 12,2 cm

AMBIENT OPERATING CONDITIONS

Humidity: 10 ... 75 %

Ambient temperature: -25 ... 45 °C

GENERAL CHARACTERISTICS

Top features: Gain in satellite range

Top features: Slope fixed correction

Top features: For Quattro-LNB

Top features: Energy saving - usable without mains adapter

Top features: Input for terrestrial signals

Top features: Suitable for DOCSIS

AMPLIFICATION

Sat: 2 ... 4 dB , bottom taps 3 ... 8 dB

Terrestrial: -15 dB

RECEPTION RANGE

Sat: 950 ... 2.150 MHz

Terrestrial: 2 ... 790 MHz

DECOUPLING

Output: > 30 dB

TECHNICAL DATA

Satellite inputs: 4

Terrestrial input: 1

Outputs: 8

Distribution length: max. 100 m

SCOPE OF DELIVERY

TECHNISWITCH 5/8 Mini, instruction manual