



## TECHNISWITCH 5/8 Mini

Compact multiswitch for distribution of 4 IF levels and terrestrial signals for 8 participants.

| EAN           | Colour      | Item no.  | Weight (Box) | Weight | Device (W x H x D)  | Box               |
|---------------|-------------|-----------|--------------|--------|---------------------|-------------------|
| 4019588032606 | blue/yellow | 0000/3260 | 200 g        | 160 g  | 7,9 x 3,3 x 11,5 cm | 9,5 x 4 x 12,2 cm |

### TOP FEATURES

- The multiswitch distributes one orbital position (4 satellite blocks) to up to 8 users, including injection of DVB-T/DAB+/FM or cable TV for analog, digital, HD, 3D operation
- All outputs are pre-compensated for slope, allowing cable lengths of up to 100 meters from LNB to antenna socket
- Package includes: 1 x TECHNISWITCH 5/8 MINI and user manual – in top quality from TechniSat
- DOCSIS signal transmission enables simultaneous use of internet and telephone services from cable providers
- Energy-efficient multiswitch is powered by the receiver and does not require an external power supply

### AMBIENT OPERATING CONDITIONS

Humidity: 10 ... 75 %

Ambient temperature: -25 ... 45 °C

### AMPLIFICATION

Sat: 2 ... 4 dB, bottom taps 3 ... 8 dB

Terrestrial: -15 dB

### DECOUPLING

Output: > 30 dB

**GENERAL CHARACTERISTICS**

Top features: Gain in satellite range

Top features: Slope fixed correction

Top features: For Quattro-LNB

Top features: Energy saving - usable without mains adapter

Top features: Input for terrestrial signals

Top features: Suitable for DOCSIS

**RECEPTION RANGE**

Sat: 950 ... 2.150 MHz

Terrestrial: 2 ... 790 MHz

**TECHNICAL DATA**

Satellite inputs: 4

Terrestrial input: 1

Outputs: 8

Distribution length: max. 100 m

**SCOPE OF DELIVERY**

TECHNISWITCH 5/8 Mini, instruction manual