



TECHNISWITCH 5/8 Mini LAN

Compact multiswitch for distribution of 4 IF levels and terrestrial signals for 8 participants. Including TECHNILAN support to distribute Internet and other network services over the existing satellite wiring

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588032613	blue/yellow	0000/3261	500 g	160 g	7,9 x 3,3 x 11,5 cm	23 x 6 x 15,2 cm

AMBIENT OPERATING CONDITIONS

Humidity: 10 ... 75 %

Ambient temperature: -25 ... 45 °C

GENERAL CHARACTERISTICS

Top features: Gain in satellite range

Top features: Slope fixed correction

Top features: For Quattro-LNB

Top features: TechniLAN suitable

Top features: Input for terrestrial signals

Top features: Suitable for DOCSIS

TECHNICAL DATA

Satellite inputs: 4

Terrestrial input: 1

Outputs: 8

Distribution length: max. 100 m

AMPLIFICATION

Sat: 2 ... 4 dB, bottom taps 3 ... 8 dB

Terrestrial: -15 dB

POWER SUPPLY

Mains adapter: Extern, DC 13 V / 3 A

Nominal voltage: 100 ... 240 V

Frequency: 50 ... 60 Hz

DECOUPLING

Output: > 30 dB

RECEPTION RANGE

Sat: 950 ... 2.150 MHz

Terrestrial: 80 ... 790 MHz

Return path: 2 ... 65 MHz

SCOPE OF DELIVERY

TECHNISWITCH 5/8 Mini LAN, instruction manual, power supply (13 V/3 A)

Test Results TECHNISWITCH 5/8 Mini LAN



Note: Sehr gut (93,9 %)
SatVision (07/2014)



Note: Sehr gut (93,9 %)
SatVision (07/2014)