



F plug Self-Install™ 4.9 set

4.9 Professional Installation kit for home

EAN	Colour	Item no.	Weight (Box)	Weight	Box
4019588633704	silver	0006/3370	100 g	100 g	12,2 x 18,7 x 2,5 cm

TOP FEATURES

Easy and safe installation in seconds

with 6 Self-Install™ F-connectors 4.9

including stripping tool

Suitable for 115dB and 120dB cables from TechniSat

Suitable for all RG6 coaxial cables 1.0/4.6

Suitable for all coaxial cables with approx. 4.5 mm dielectric and 6.6 - 7.0 mm outer diameter

ATTENUATION

10 MHz: 0,03

100 MHz: 0,03

450 MHz: 0,03

800 MHz: 0,05

862 MHz: 0,06

1000 MHz: 0,06

2250 MHz: 0,06

RETURN LOSS

30 - 65 MHz: ≥ 38 dB

65 - 470 MHz: ≥ 38 dB

470 - 1800 MHz: ≥ 26 dB

1800 - 2450MHz: ≥ 26 dB

TECHNICAL DATA

Impedance: 75 Ω

TRANSFER IMPEDANCE

5MHz: ≤ 0,2

30 MHz: ≤ 0,2

SCOPE OF DELIVERY

6 x F-connectors Self-Install™ 4.9<CRLF>1 x stripping tool<CRLF>