



## TECHNIROUTER 5/1x8 G-R

TECHNIROUTER base unit, suitable for the return path. It enables the connection of 4 IF levels (satellite blocks) and a terrestrial input for cable harness distribution for 8 participants

Colour	EAN	Item no.	Weight	Device (W x H x D)	Box
silver/yellow	4019588132900	0001/3290	340 g	14 x 11,5 x 3,2 cm	24,5 x 13,5 x 5,5 cm

### FILTER-NAVIGATION

Number participants: 8

### AMBIENT OPERATING CONDITIONS

Humidity: 10 ... 75 %

Ambient temperature: -25 ... 55 °C

### AMPLIFICATION

Sat: 13 ... 18 dB

Terrestrial: -1 dB

### DECOUPLING

Trunks: 45 dB

### GENERAL CHARACTERISTICS

Top features: DiSEqC protocol according to EN 50494

Top features: 1 orbit position without restrictions

Top features: Return path compatible

Top features: No new wiring required

Top features: Energy-saver - can be used without power supply

### POWER SUPPLY

Power consumption: 210 mA @13V (SCR-Ausgang, ohne LNB)

Mains adapter: external DC 12V/0,46A (nur für LNB + Terrestrik)

#### RECEPTION RANGE

Return path: 5 ... 65 MHz

Terrestrial: 65 ... 862 MHz

Sat: 950 ... 2.150 MHz

#### SINGLE-CABLE OUTPUT

Output frequency: 5 ... 2.150 MHz

Number of output channels: 8

Frequency of the output channels: 1284, 1400, 1516, 1632, 1748, 1864, 1980, 2096 MHz

Frequency SAT: 950 ... 2.150 MHz

Frequency DVB-T: 65 ... 862 MHz

#### TECHNICAL DATA

Satellite inputs: 4

Terrestrial input: 1

Number of cable connections: 1

Subscribers per cable: maximal 8

#### TUNER

TECHNIROUTER ready: Yes

#### SCOPE OF DELIVERY

TECHNIROUTER5/1x8 G-R, user manual, power adapter<br><br>