



TECHNIROUTER 5/2x4 G-R

Digital single-cable solution for the distribution of satellite signals from one orbital position via two cable harnesses for an existing cable structure

Colour	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
silber/gelb	4019588132924	0001/3292	500 g	200 g	14 x 11,5 x 3,2 cm	24,5 x 13,5 x 5,5 cm

AMBIENT OPERATING CONDITIONS

Humidity: 10 ... 75 %

Ambient temperature: -25 ... 55 °C

GENERAL CHARACTERISTICS

Top Features: DiSEqC according to EN 50494

Top Features: 1 orbit position without restrictions

Top Features: Return channel compatible

Top Features: No new wiring required

Top Features: Can be used to save energy without a power supply unit

SINGLE-CABLE OUTPUT

Output frequency: 5 ... 2.150 MHz

Number of output channels: 2 x 4

Frequency of the output channels: 1284, 1400, 1516, 1632 MHz

Frequency SAT: 950 ... 2.150 MHz

Frequency DVB-T: 65 ... 862 MHz

AMPLIFICATION

Sat: 17 ... 22 dB

Terrestrial: -5 dB

POWER SUPPLY

Power consumption: 210 mA @13V (je SCR-Ausgang, ohne LNB)

Mains adapter: external DC 12V/0,46A (nur für LNB + Terrestrik)

TECHNICAL DATA

Satellite inputs: 4

Terrestrial input: 1

Number of cable connections: 2

Subscribers per cable: maximal 4

DECOUPLING

Trunks: 45 dB

RECEPTION RANGE

Return path: 5 ... 65 MHz

Terrestrial: 65 ... 862 MHz

Sat: 950 ... 2.150 MHz

TUNER

TECHNIROUTER ready: Yes

SCOPE OF DELIVERY

TECHNIROUTER5/2x4 G-R, manual, power supply
