



DIGIT ISIO S2

HDTV satellite receiver with twin tuner

Hard drive	Colour	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
extern	black anodised	4019588047563	0000/4756	1,6 kg	900 g	28,6 x 4,6 x 15,5 cm	37,2 x 8,4 x 17,6 cm

TOP FEATURES

HDTV twin tuner (DVB-S/S2)

DVRready for recording on USB storage device or network attached storage (NAS)

Timeshift in connection with USB hard drive

ISIO internet: Access to media libraries, ISIO apps and HbbTV

Multimedia streaming on home network (via UPnP)

Steuerung per CONNECT-App

Pay TV compatible via CI+

Control by CONNECT app

MULTIMEDIA

DVR function: Ja

DVR storage medium: via USB

Timeshift: Yes

Recordings edition function: Yes

Recordings folder management: Yes

AMBIENT OPERATING CONDITIONS

Humidity: 10 ... 75 %

Ambient temperature: 5 ... 35 °C

LNB CONTROL

Vertical: 14 V

Horizontal: 18 V

Band switch: 22 kHz

Current consumption: max. 400 mA (kurzschlussfest)

DiSEqC: 1.0 / 1.2 / SCR1 / SCR2

TECHNISAT ADDED VALUE SERVICES

ISIPRO: Yes

TECHNIFAMILY: Yes

AUTOINSTALL: Yes

TECHNIMATIC: Yes

SFI: Yes

INTERNET/NETWORK

Webbrowser: Yes

Internet speed test: Yes

HbbTV: Yes

ISIO Internet: Yes

HTML 5 support: Yes

AUDIO

AC3 Dolby Digital bitstream out: Yes

Clear language from ARD: Yes über DVB

CARD READER

SD card: Yes

CONNECTIONS

HDMI™ (out): 1

USB: 3 (USB 2.0)

Common Interface Plus (CI+): Yes

Smartcard reader: Yes

Digital electric audio output (S/PDIF): Yes

Digital optical audio out: Yes

Audio out analogue (RCA): Yes (rechts / links)

Scart: 1 Mini SCART (0000/3602)

Ethernet 10/100 (RJ-45): Yes

F socket: 2

Connector for external IR-Receiver: 1

DC IN: 1

DECODER

Video decoder: MPEG-2 MP@HL/ML, H.264/MPEG-4 AVC

Audio decoder: MPEG-1 & MPEG-2 Layer I, II, III

DECRYPTION SYSTEM

Conax: Yes

CI+: Yes

DISPLAY

Picture in Picture (PIP): Yes (2x HD, 2x SD, 1x SD u. 1x HD)

Picture and Picture (PAP): Yes

Freeze frame: Yes

Zoom: Yes

SD: Yes

HD: Yes

1080p: Yes

1080i: Yes

720p: Yes

576p: Yes

576i: Yes

Type: VF-Display

HANDLING/COMFORT

Page memory: 1.000

Teletext: Yes

Teletext subtitles: Yes

Media Player: Yes

Clock: Yes

Sleep timer: Yes

Alarm: Yes

Ideal for camping: Yes

Autostandby: Yes

Remote control: Yes

Hotel mode: Yes

Quick start: Yes

Channel presets: 10.000

Selection regional channels: Yes

HOTEL MODE

Protected access to hotel mode: Yes

Customisable start screen: Yes

Lockable volume: Yes

Menu locking: Yes

Control panel lock: Yes

Integrated LED clock: Yes

Selectable start source: Yes

Selectable start channel: Yes

NETWORK & COMMUNICATION

TCP/IP: Yes

IPv4: Yes

DHCP: Yes

HTTP: Yes

UPnP: Yes

100Base-T: Yes

OTHER FEATURES

OSD languages: English, German, French, Greek, Italian, Dutch, Polish, Portuguese, Russian, Swedish, Spanish, Czech, Turkish, Hungarian

POWER CONSUMPTION

Standby fast start: 8,4 W

Standby LED: < 0,37 W

In operation: 13 W

POWER SUPPLY

Mains adapter: external DC 12 V / 3 A

Nominal voltage: 230 V

Frequency: 50 Hz

STREAMING

DLNA Server: Yes

Cloud store: Ja

Parental Control: Yes

DLNA Client: Yes

SUPPORTED FORMATS & CODECS

Video-Codecs: MPEG-2, MPEG-4, MPEG-1, H.264

Video-Formats: MKV, MP4, MOV, MPG, TS, TS4, VOB, WMV, AVI, ASF

Picture-Formats: BMP, JPEG, GIF, PNG, TIFF

Audio-Formats: WAV, MP3, AAC, FLAC, M4A, MP2, OGG, DDAC3

TECHNISAT CONNECT

SFI: Yes

TUNER

Tuner type: Twin-Tuner

DVB-S tuner: 2

Single Cable Solution (SatCR): SCR1 = EN50494, SCR2 = EN50607

Satellite radio: Yes

Reception on: HD-TV, SD-TV

TECHNISELECT 12 ready: Yes

TECHNIROUTER ready: Yes

TUNER - SAT

Reception range: 950 ... 2.150 MHz

Viterbi rates: 1/2, 2/3, 3/4, 5/6, 7/8 , (autom. Anpassung)

DVB-S: QPSK

DVB-S: 2 ... 45

DVB-S2: 8PSK-QPSK

DVB-S2: 10 ... 31

FEC: Viterbi and Reed-Solomon

SCOPE OF DELIVERY

DIGIT ISIO S2, TECHNICONTRON remote control with batteries, external mains adapter, HDMI cable, Instruction manual, warranty card

Test Results DIGIT ISIO S2



Note: Sehr gut (93,5%)
SATVISION (09/2014)



KAUF TIPP
SFT (11/2014)

Stiftung Warentest
Heft 6/2015

Testsieger (zusammen mit
einem weiteren Gerät)
Testurteil gut (2,3)
Im Test: 12 Sat-Empfänger



Testurteil: Sehr gut (1,3)
SFT (11/2014)