



Line Amplifier 9Z2

Amplifier for signal gain for 2 orbital positions

Colour	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
silver/yellow	4019588232310	0002/3231	280 g	190 g	20,8 x 5,5 x 3,2 cm	25,2 x 7,4 x 4,7 cm

LNB CONTROL

Current consumption: max. 850 mA

AMBIENT OPERATING CONDITIONS

Ambient temperature: -25 ... 55 °C

AMPLIFICATION

Sat: 15 ... 20 dB fest, schräglagenentzerrt

Terrestrial: 7 ... 14 dB einstellbar

Return path: -1 dB

DECOUPLING

Trunks: 50 dB

GENERAL CHARACTERISTICS

Top features: Kompensiert die Dämpfung von bis zu 60 m Koaxkabel

Top features: Rückkanaltauglich von 2...68 MHz

Top features: Optionale Stromversorgung über Steckernetzteil

Top features: Gleiches Rastermass der F-Buchsen wie GigaSwitch 9/8 und TechniRouter 9/8

POWER CONSUMPTION

In operation: 5,5 W

POWER SUPPLY

Nominal voltage: 15 V DC

Mains adapter: external (Optional)

Power consumption: typ. 340 mA @15 V

RECEPTION RANGE

Sat: 950 ... 2.150 MHz

Terrestrial: 87 ... 790 MHz

Return path: 2 ... 68 MHz

TECHNICAL DATA

Satellite inputs: 8

Terrestrial input: 1

SCOPE OF DELIVERY

Line Amplifier 9Z2, instruction manual